

# NAPCO ANTI-SLIP SOLUTION

## Product Description

NAPCO Anti-Slip Solution is a waterborne, low VOC, permanent anti-skid product. It is a penetrating agent that renders dangerous, slippery porcelain or enamel bathtubs, tile floors, marble, and granite safer wet than dry. This translucent pink liquid is environmentally safe, non-flammable, and non-hazardous. It is not a coating, requires no special maintenance, and causes no significant change in the surface's appearance. Anti-Slip Solution does not leave a gritty, uncomfortable surface.

## Test Data

The Ceramic Tile Institute identifies tile in the following 3 categories: Slip Resistant (individual static coefficient of friction of 0.60 or greater), Conditionally Slip Resistant (individual static coefficient of friction of 0.50 to 0.59), and Questionable (individual static coefficient of friction of 0.49 or less).

When a glazed tile treated with NAPCO Anti-Slip Solution was tested against dry leather and dry rubber (common shoe materials), the individual static coefficient of friction was found to be 0.48 (Questionable) and 0.68 (Slip Resistant), respectively.

When a glazed tile treated with NAPCO Anti-Slip Solution was tested against wet leather and wet rubber, the individual static coefficient of friction was even greater - 0.65 (Slip Resistant) and 0.71 (Slip Resistant), respectively. Surfaces treated with NAPCO Anti-Slip Solution are even more slip resistant when wet than when dry.

Under the standards of the Ceramic Tile Institute, wet tile and porcelain surfaces treated with Anti-Slip Solution are rated as "Slip Resistant" - the highest safety rating possible.

## Equipment and Application

No special tools are required. Clean the surface. Apply NAPCO Anti-Slip Solution with a lint free cloth, foam brush, mop, or simply spray it on the surface. Make sure to completely cover the surface with NAPCO Anti-Slip Solution. Allow the NAPCO Anti-Slip Solution to dry (approximately 20 minutes), and then rinse the surface with water. No secondary application is necessary.

## Coverage

NAPCO Anti-Slip Solution will cover approximately 1,000 square feet per gallon. One gallon of NAPCO Anti-Slip Solution will cover 128 bathtub floors.

## **Limitations**

NAPCO Anti-Slip Solution is not effective on plastic or fiberglass surfaces. NAPCO Anti-Slip Solution must not be used on resurfaced fixtures or floors.

## **Maintenance**

Occasional cleaning is required. There is no need for special non-abrasive cleaners.

## **Cautions**

Keep out of the reach of children.

This material is acidic and hazardous if ingested. Serious damage is possible to mouth, esophagus, and stomach. If ingested, drink a quart of water and do not induce vomiting. Obtain medical attention immediately.

If NAPCO Anti-Slip Solution comes in contact with the eyes, flush eyes with water for 15 minutes. If irritation persists, see a physician.

If NAPCO Anti-Slip Solution causes skin irritation, wash affected skin well with water and soap.

## **Technical Support**

MSDS is available upon request. NAPCO's technical service department is open between 7:30 a.m. and 5:00 p.m. Central Time Monday through Friday. For technical assistance, call 1-800-888-1081.

## **Warranty**

The Manufacturer (NAPCO) warrants only that the product shall meet its specifications. This warranty is in lieu of all other written or unwritten, expressed or implied warranties and the Manufacturer expressly disclaims any warranty of merchantability, or fitness for a particular purpose. The buyer assumes all risks whatsoever as to the use of the material.

Buyer's exclusive remedy as to any breach of warranty, negligence or other claims shall be limited to the replacement of the material. Failure to strictly adhere to recommended procedure shall release the Manufacturer with respect to the material or the use thereof.

© Copyright – Ameriglaze and North American Polymer Company, Ltd. - 2005  
7315 Hamlin Av., Skokie, IL 60076 USA  
info@napcoltd.com  
All rights reserved. No reproduction without permission.