



POLY-GLASS® 320 LOW GLOSS RESIN

EQUIPMENT, SUPPLIES, AND TRAINING FOR THE PROFESSIONAL REFINISHER

Since 1979 NAPCO has been making bathtub refinishers happy.

We offer the highest quality refinishing coatings and equipment to get the job done right – the first time. Your ordering experience will be a breeze with our professional customer service.

You can rely on us for bath tub resurfacing expertise so you get the right product for your specific situation. Order your countertop and tub refinishing supplies and equipment online, 24/7. We offer the industries best hands-on bathtub, tile, sink and counter top reglazing training in convenient 2-day classes.

**North American
Polymer Company, LTD.**

7315 Hamlin Avenue
Skokie, IL 60076.3902
800.888.1081

Poly-Glass 320 is an eco-friendly topcoat that meets federal guidelines for low VOC's. It offers all the benefits of earlier coatings but with low VOCs, and the odor is greatly reduced. This product is better for you, better for your customers, and better for your business. It's easy to use, the finish is just as hard as or harder than conventional coatings, and it's safer for you and your customers.

APPLICATION: This is a 2 component Aliphatic Acrylic Polyurethane Resin. Mix 2 parts Poly-Glass® 320 Resin with 1 part Poly-Glass® 320 Catalyst. For the average sized bathtub (or 35 square foot surface), mix 10 oz. of Poly-Glass® 320 Resin with 5 oz. Poly-Glass 320 Catalyst (by volume). Thin with 5 to 9 oz. of NAPCO 320 Medium Speed Thinner. Spray 1 light tack coat followed by 2 wet coats. Pause between coats to inspect work. Dries to the touch in 5 to 15 minutes with normal humidity and temperature. Remove masking paper and apply caulk in 15 to 30 minutes. Air cured, water resistant in 2 hours at 75°F.

STORE INDOORS BETWEEN 50-90°F
Shake constantly for 15 - 30 seconds before using.

