



Technical Data Sheet

Kitchen Renew Color Dispersions

Paint Additive

Description

NAPCO's Kitchen Renew Color Dispersions are added to Kitchen Renew products to provide color matching for a full refinish job, or for spot repair use when color matching a damaged portion of a countertop or cabinet. NAPCO currently provides thirteen different Kitchen Renew Color Dispersions so you can match customer requests for any color.

Laboratory Data	Typical Properties
Appearance	Liquid – Various Colors
Flash Point	>212°F
Density (lbs./gal.)	Various

Application

Use in a well-ventilated area and use the necessary Personal Protective Equipment (safety glasses/goggles, gloves, respirator, fresh air breathing apparatus) as appropriate.

Surface Preparation

Depending on the refinish coating, the surface should be cleaned and prepped accordingly.

Mixing Instructions

Kitchen Renew Color Dispersions should be shaken for approximately 10 seconds before use to ensure homogeneity.

7315 Hamlin Avenue - Skokie, IL 60076-3902 - Phone (847) 779-6464 - Toll Free: (800) 888-1081

Temperature/Humidity Considerations

Application temperatures between 50°F and 90°F are recommended for best performance.

Notes and Precautions

Refer to the SDS before use. Obtain special instructions before use. Do not handle until all

safety precautions have been read and understood. Use personal protection recommended in Section 8. Use only in well-ventilated areas. Wash face, hands and any exposed skin thoroughly after handling. Keep away from heat/sparks/open flames/hot surfaces. — No smoking. Use spark-proof tools and explosion-proof equipment. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Do not breathe vapors or spray mist. Ground/bond container and receiving equipment.

Storage

Keep containers tightly closed in a dry, cool and well-ventilated place. Store away from heat, sparks, flame. Store locked up.

12/18 - SAZ