



Technical Data Sheet

On The Spot Gun Cleaner

Paint Cleaner

Description

Our On The Spot Gun Cleaner works almost immediately due to its formulation of effective, powerful solvents without the use of methylene chloride. Hard surfaces like marble, tile, porcelain, or glass can be cleaned instantly with On The Spot. It is especially efficient in cleaning overspray from these surfaces. Additionally, any silicone contamination present on surfaces is easily removed using On The Spot and you can use it to clean your spray system of any residual paint.

Be safer by using our new methylene chloride-free On The Spot Gun Cleaner! Make sure to use at least a cartridge respirator with organic vapor cartridges installed.

Laboratory Data

Typical Properties

Appearance	Clear Liquid
Specific Gravity	0.841
Flash Point (closed cup)	3.2°F

Application

Chemical resistant gloves (Viton, polyvinyl alcohol, or polyfluorinated polyethylene) and safety goggles should be worn when handling in a well-ventilated area. Do not breathe vapor. Use a NIOSH approved respirator where mist, spray, or vapor is generated and exceeds PEL. Avoid contact with eyes, skin, and clothing. Do not use in closed or confined spaces. If ventilation equipment is used, it must be explosion proof.

7315 Hamlin Avenue - Skokie, IL 60076-3902 - Phone (847) 779-6464 - Toll Free: (800) 888-1081

Fax (847) 779-6465 - www.napcoltd.com

Surface Preparation

Surfaces should be completely dry prior to cleaning off overspray and/or cleaning guns.

Temperature/Humidity Considerations

For best results, use in temperatures between 65°F and 85°F and away from strong breeze and hot sun.

Notes and Precautions

Handle in accordance with good industrial hygiene and safety practice. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protection recommended in Section 8. Wash face, hands and any exposed skin thoroughly after handling. Do not eat, drink or smoke when using this product. Use only in well-ventilated areas. Avoid breathing vapors or mists. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). All equipment used when handling the product must be grounded. Use non-sparking hand tools and explosion-proof electrical equipment. Take precautionary measures against static discharges.

Storage

Do not store where zinc and aluminum are used. Ground containers when transferring liquids to prevent static accumulation. Empty containers should be completely drained properly bunged and returned to supplier or disposed of in an environmentally safe manner. **STORE INDOORS BETWEEN 50-90°F**